

GT360 - GameTime Projector

Big Screen Gaming – Be Part of the Action

Elevate your gaming experience with Optoma's GT360. Designed from the ground up for gaming enthusiasts, the GT360's maximum screen size goes up to 300" for an impressive big screen display of games, movies, television or computer content. The portable GT360 comes with its own backpack to bring your gaming fun wherever you go. The GT360 is 3D Ready and displays amazingly life-like images when connected to a 3D gaming or video source and the projection is viewed with 3D active glasses.

*3D source, 3D content and 3D glasses are required for 3D viewing



Features

- DLP® Link™ 120Hz 3D Ready display technology
- Bright at 2500 ANSI lumens with a high contrast ratio of 3000:1
- Projects 150" diagonal image at about nine feet
- Supports resolutions up to 1080p
- Powerful audio – built-in 10-watt speaker system
- Flexible connections – VGA, S-video, Composite, Stereo RCA Audio-in, Stereo Audio-out & RS-232

Display Technology

Single 0.55" DC3 DMD DLP® Technology by Texas Instruments

Resolution

Native SVGA (800 x 600)

Maximum Resolution

UXGA (1600 x 1200), 1080p

Brightness (Typical)

2500 ANSI Lumens

Contrast Ratio

3000:1 (Full On/Full Off)

Lamp Life and Type

5000/3000 Hours (STD/Bright)
180W P-VIP

Throw Ratio

0.9:1 (Distance/Width)

Image Size (Diagonal)

27" to 300" (0.68m to 7.62m)

Projection Distance

1.64' to 18.0' (0.5 to 5.5 m)

Remote Control

IR Remote Control

Aspect Ratio

4:3 Native, 16:9 Compatible

Keystone Correction

± 15° Vertical

Uniformity

85%

Computer Compatibility

UXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, C and Macintosh Compatible

3D Computer Compatibility (120Hz)

SVGA (800 x 600)
XGA (1024 x 768)
HD (1280 x 720)

Video Compatibility

NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (576i/p, 720i/p, 1080i/p)

3D Video Compatibility

SDTV (480i)

Projection Lens

F=2.55, f=10.19mm

Projection Method

Front, Rear, Ceiling Mount, Table Top

User Controls

Complete On-Screen Menu Adjustments in 20 Languages

Security

One Kensington® Lock, Security Bar and Keypad Lock

I/O Connectors

VGA-In, S-Video, Composite Video, Stereo RCA Audio-In, Stereo Audio-out & RS-232

Dimensions (W x H x D)

12.76" x 3.82" x 9.21"
(324 x 97 x 234 mm)



Weight

6.5 lbs (2.95 kg)

Noise Level (STD/Bright)

28dB/30dB

Operating Temperature

41-104°F (5-40°C), 80% Max Humidity

Power Supply

AC Input 100 - 240V, 50-60HZ, Auto-Switching

Power Consumption

255 Watts (Bright), 233 Watts (STD) <1 Watt (Standby)

Standard Accessories

AC Power Cord, VGA to Component Adapter, Remote Control, Batteries for Remote, Lens Cap, Backpack, Quick Start Guide, Warranty Card, and Multilingual User's Manual

Optional Accessories

Carrying Case, Ceiling Mount, VGA Cable, VGA to Component Cable, S-Video Cable and Panoview™ Series Screens

Warranty

1 Year Limited Parts and Labor, 90 Days on Lamp

UPC

796435 81 115 0